

Double Drive Over/Truck Unloader Conveyor STANDARD

42 x 50

- Structure
 - 10" I-Beam Horizontal Body
 - 1/4" Diamond Plate Top
 - 1/4" Plate Bottom Skid
 - 3/16 Belt Pan
 - Removable Ramps – 4 each
 - 48" Wide – 16 ft Long – Diamond Plated
 - 8" Channel Inclined Structure
 - 3/16 Flat Pan
 - Roller Troughing Idlers
- Lagged Drive Pulley 18" Dia.
 - 2 7/16" Shaft
 - Roller Bearings
- Winged Tail - 6" Dia.
 - 2 7/16" Shaft
 - Roller Bearings
 - Tubular Screw Take-ups
- Dual Drive
 - World Wide #4 Drive
 - Motor Mount
 - Belt Guard
 - 2 x 10 hp, TEFC, 1800 RPM, 230/460 volt
- **Full Voltage Double Motor Starter**
- **Electric-Hydraulic Jack/Cylinder Package**
- 42" x 52" Opening w/Grate
- Belt – Bare Back Chevron
- 16" Hold-Down Wheel
- Tail Guard
- Primed & Painted, Green



PRICE.....\$ 52,100.00

Terms:.....25% with order, remainder C.O.D. prior to shipment
 F.O.B.....Boswell, PA